

GLIN GLT 68 S

Profile dimension	Installation depth	68 mm
	Visible width - left and right	123 mm
	Visible width - down side	150 mm
Installation options	Rectangular	*
	Oblique	
	Arched, semicircular	
Opening options	Fixed	
	Combined, OW and TW	*
	Folding walls	
	Tilt-slide walls	
	Lift-slide walls	
Glazing	Double	*
	Triple	
Thermal insulation of the window (Uw)	Ug = 1,1	1,4 W/m ² K
Number of seals	Permanently elastic seal	1
Surface treatment	Basic impregnation	*
	Final coating	
Alu rain protection	On the frame	*
	On the wing	

* what window content

WOOD

High quality wood spruce/larch. Humidity of wood is 12 +/-2%

Profils are glued from more layers with water resistant glue, typ D4

Two perpetual surface layers.

HARDWARE

ROTO NT - silver, one-handed opening in the vertical and horizontal axis.

STANDARD DIMENSIONS

Windows - one wing (OW)

60 x 60
60 x 90
80 x 60
80 x 90
80 x 120
80 x 140
100 x 90
100 x 100
100 x 120
100 x 140
120 x 90
120 x 120
120 x 140
140 x 90
140 x 120
140 x 140

Windows - two wings (TW)

100 x 120
100 x 140
120 x 120
120 x 140
140 x 90
140 x 120
140 x 140
160 x 140
180 x 120 - asimetric
180 x 140 - asimetric

Balcony door (OW)

80 x 210
80 x 220
80 x 230
100 x 210
100 x 220
100 x 230

Balcony door (TW)

140 x 210
140 x 220
140 x 230