

## GLIN GLT 68 ALU EV

<b>Profile dimension</b>	Installation depth	85 mm
	Visible width - left and right	119 mm
	Visible width - down side	146 mm
<b>Installation options</b>	Rectangular	*
	Oblique	*
	Arched, semicircular	*
<b>Opening options</b>	Fixed	*
	Combined, OW and TW	*
	Folding walls	*
	Tilt-slide walls	*
	Lift-slide walls	*
	Opening on outside	*
	Both side handle	*
<b>Glazing</b>	Double	
	Triple	*
<b>Thermal insulation of the window (Uw)</b>	Ug = 0,7 - Alu spacer	1,1 W/m <sup>2</sup> K
	Ug = 0,7 - TGI spacer	1,0 W/m <sup>2</sup> K
	Ug = 0,5 - TGI spacer	0,90 W/m <sup>2</sup> K
<b>Number of seals</b>	Permanently elastic seal	2
<b>Surface treatment</b>	Basic impregnation	*
	Final coating	*
<b>Alu rain protection</b>	On the frame	*
	On the wing	

\* contain

### WOOD

High quality wood spruce/larch. Humidity of wood is 12 +/-2%

Profiles are glued from more layers with water resistant glue, typ D4

Two perpetual surface layers

### HARDWARE

ROTO NT - silver, one-handed opening in the vertical and horizontal axis.

Hidden hardware and covering caps are possible.

### ALU MASK

Alu masks are fixed on the wing and on the frame in a way they don't disturb ventilation.

Alu mask providing the weather protection and modern appearance.

We offer alu masks in wide range of different colours and decors.