

GLIN PASIV 92 ALU PLUS

Profile dimension	Installation depth	107 mm
	Visible width - left and right	117 mm
	Visible width - down side	132 mm
Installation options	Rerctangular	*
	Oblique	*
	Arched, semicircular	*
Opening options	Fixed	*
	Combined, OW and TW	*
	Folding walls	*
	Tilt-slide walls	*
	Lift-slide walls	*
	Opening on outside	*
	Both side handle	*
Glazing	Double	
	Triple	*
Thermal insulation of the window (Uw)	Ug = 0,6 - TGI spacer	0,74 W/m ² K
	Ug = 0,5 - TGI spacer	0,67 W/m ² K
Number of seals	Permanently elastic seal	3
Surface treatment	Basic impregnation	*
	Final coating	*
Alu rain protection	On the frame	*
	On the wing	

* contain

WOOD

High quality wood spruce/larch. Humadity of wood is 12 +/-2%

Profils are glued from more layers with water resistant glue, typ D4

Two perpetual surface layers

HARDWARE

ROTO NT - silver, one-handed opening in the vertical and horizontal axis.

Hidden hardware and covering caps are possible.

ALU MASK

Alu masks are fixed on the wing and on the frame in a way they don't disturb ventilation.

Alu mask providing the weather protection and modern apperance.

We offer alu masks in wide range of different colours and decors.

INFILL

There is a thermal insulated material built in wooden profil, which improve a lot total thermal insulation of window (Uw)

