

## GLIN PASIV 92

<b>Profile dimension</b>	Installation depth	92 mm
	Visible width - left and right	119 mm
	Visible width - down side	134 mm
<b>Installation options</b>	Rerctangular	*
	Oblique	*
	Arched, semicircular	*
<b>Opening options</b>	Fixed	*
	Combined, OW and TW	*
	Folding walls	*
	Tilt-slide walls	*
	Lift-slide walls	*
	Opening on outside	*
	Both side handle	*
<b>Glazing</b>	Double	
	Triple	*
<b>Thermal insulation of</b>	Ug = 0,6 - alu spacer	0,94 W/m <sup>2</sup> K
	Ug = 0,6 - TGI spacer	0,86 W/m <sup>2</sup> K
	Ug = 0,5 - TGI spacer	0,77 W/m <sup>2</sup> K
<b>Number of seals</b>	Permanently elastic seal	3
<b>Surface treatment</b>	Basic impregnation	*
	Final coating	*
<b>Alu rain protection</b>	On the frame	*
	On the wing	*

\* contain

### WOOD

High quality wood spruce/larch. Humadity of wood is 12 +/-2%

Profils are glued from more layers with water resistant glue, typ D4

Two perpetual surface layers

### HARDWARE

ROTO NT - silver, one-handed opening in the vertical and horizontal axis.

Hidden hardware and covering caps are possible.